

# Technical Specifications

| Model t702k                          | PL461AA   |
|--------------------------------------|---|
| <b>Processor &amp; Speed</b>         | Intel® Celeron® (P)330 Processor – 2.66 GHz/533 PGA478  |
| <b>Chipset</b>                       | Intel® 865G   |
| <b>Motherboard</b>                   | Cobra-GL6E (4PSD-LA)  |
| <b>RAM</b>                           | 256/3200 MB 400DDR SDRAM (runs@333MHz)  |
| Maximum                              | 3 GB  |
| Sockets                              | Four 184-pin DDR DIMMs  |
| Size                                 | 128, 256 and 512 MB DDR DIMMs   |
| <b>Free DIMM Sockets</b>             | Three   |
| Pairs Required                       | No  |
| Type Supported                       | JEDEC unbuffered DDR SDRAM DIMM specification   |
| <b>Cache</b>                         | 16KB Data Cache + Trace Cache L1, 256 KB L2 Integrated on Processor module                        |
| <b>Hard Drive</b>                    | 160 GB (7200 RPM)   |
| <b>Optical Drive</b>                 | CD-RW/DVD-ROM Drive 48x32x16x48<br>48X- Write /32X - Re-write /16x- DVD Read<br>48X - CD-ROM Read |
| Average Random Access                | DVD =115ms / CD-ROM =95ms   |
| Transfer Rate                        | DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.   |
| <b>Diskette Drive</b>                | None  |
| <b>9 in 1 Card Reader</b>            | Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart Media, xD, Microdrive                         |
| <b>Video Graphics</b>                | Intel® Extreme Graphics   |
| Controller                           | Integrated w/865G Chipset   |
| Video Memory                         | 64MB UMA  |
| <b>Network Card</b>                  | 10/100 BaseT, Integrated  |
| <b>1394 Card</b>                     | IEEE-1394, Integrated   |
| <b>Sound</b>                         | AC'97, 6 Channel, Integrated on MB  |
| Controller                           | Realtek ALC650  |
| <b>Chassis</b>                       | Jaguar, 250HV PSU   |
| <b>USB Interface Specification</b>   | USB 2.0   |
| <b>External I/O</b> Rear Connectors  | 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone                                   |
| <b>External I/O</b> Front Connectors | 2=USB; 1= 1394, Line In, Microphone, Headphone, 9 in 1 Card Reader w/USB                          |
| <b>Expansion Slots (Total)</b>       | 3= PCI, 1= AGP  |
| <b>Expansion Slots (FREE)</b>        | 3= PCI, 1= AGP  |
| <b>Drive Bays (Total)</b>            | Two 5.25" external, One 3.5" external, Two 3.5" internal  |
| <b>Drive Bays (FREE)</b>             | One 5.25" external, One 3.5" external, One 3.5" internal  |
| <b>Keyboard/Mouse</b>                | One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse   |

Copyright Hewlett-Packard Co. 1994-2004  
This information is subject to change without notice and is provided "as is" with no warranty.  
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.